



COMMERCIAL-GRADE FEATURES MAKE IT TOP-OF-THE-LINE IN RESIDENTIAL ZERO-TURNS.



10-GAUGE WELDED DECK

Design that's 5 ½-inches deep with a reinforced leading edge provides the airflow needed to tackle tough mowing conditions.

INDUSTRY LEADING FRAME DESIGN

Large formed tubular frame rails serve as the backbone to support the loads of the machine.

LARGE TIRES

Category leading large tires proving superior traction and ride quality.

CONSTANT BELT TENSION SYSTEM (CBT)

Minimizes wear and heat while providing enhanced belt life with minimal adjustments necessary.

MAINTENANCE-FREE ALUMINUM SPINDLES

Reducing bearing temperature for cooler operation.

FOOT-OPERATED DECK LIFT SYSTEM

Effortless adjustments between 15 cutting positions.

HIGH-BACK SEAT

Enhances operator comfort and reduces fatigue

ROPS CAPABLE DESIGN

Frame supports a folding ROPS option for added protection to the operator.

FLIP-UP SIDE DISCHARGE CHUTE

Reduces damage to the surrounding environment.







DESIGNATION	APEX 48	APEX 52	APEX 60	APEX 60
MODEL #	991153	991155	991157	991151
ENGINE	Kohler® 7000 Series	Kohler® 7000 Series	Kohler® 7000 Series	Kawasaki® FR Series
HORSEPOWER	23	23	25	24
DISPLACEMENT (cc)	725	725	725	726
DRIVE SYSTEM	Hydro-Gear® ZT3100 Transaxles	Hydro-Gear® ZT3100 Transaxles	Hydro-Gear® ZT3100 Transaxles	Hydro-Gear® ZT3100 Transaxles
FUEL CAPACITY	5 Gallon (18.9 L)	5 Gallon (18.9 L)	5 Gallon (18.9 L)	5 Gallon (18.9 L)
GROUND SPEED (APPROXIMATE MPH) (FWD/REV)	8 mph / 4 mph	8 mph / 4 mph	8 mph / 4 mph	8 mph / 4 mph
STARTER	Electric	Electric	Electric	Electric
DECK MATERIAL	10ga Steel	10ga Steel	10ga Steel	10ga Steel
DECK CONSTRUCTION	Fabricated	Fabricated	Fabricated	Fabricated
NUMBER OF SPINDLES	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	17,500	18,000	18,000
SPINDLE MATERIAL	Aluminum	Aluminum	Aluminum	Aluminum
SPINDLE SHAFT	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Ogura®	Electric Ogura®	Electric Ogura®	Electric Ogura®
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	48 in	52 in	60 in	60 in
CUTTING POSITIONS	15	15	15	15
WHEELS (FRONT)	13 x 6.5 in - 6 in	13 x 6.5 in - 6 in	13 x 6.5 in - 6 in	13 x 6.5 in - 6 in
WHEELS (BACK)	22 x 10 in - 12 in	22 x 10.5 in - 12 in	22 x 12 in - 12 in	22 x 12 in - 12 in
SEAT	High Back Comfort w/ Seat Springs, Lever Adjust, Arm Rests	High Back Comfort w/ Seat Springs, Lever Adjust, Arm Rests	High Back Comfort w/ Seat Springs, Lever Adjust, Arm Rests	High Back Comfort w/ Seat Springs, Lever Adjust, Arm Rests
HOUR METER	Standard	Standard	Standard	Standard
WARRANTY (MACHINE)	3 Year Limited Consumer / 1 Year Limited Commercial	3 Year Limited Consumer / 1 Year Limited Commercial	3 Year Limited Consumer / 1 Year Limited Commercial	3 Year Limited Consumer / 1 Year Limited Commercial
WARRANTY (DECK & FRAME)	5 Year Limited	5 Year Limited	5 Year Limited	5 Year Limited
WEIGHT	823 lbs	832 lbs	853 lbs	853 lbs
LENGTH	71.5 in	74.5 in	74.5 in	74.5 in
WIDTH	50 in (w/o chute)	55.5 in (w/o chute)	62.8 in (w/o chute)	62.8 in (w/o chute)
HEIGHT	42 in	42 in	42 in	42 in
ATTACHMENTS & ACCESSORIES	Powered Bagger Kit, Mulching Kit, Striper Kit, Discharge Cover Kit, Trailer Hitch Kit, Headlight Kit, Sun Shade, Spreader Cart, Roller, Aerator, Dethatcher, Sprayer, Seat Isolator Kit, Seat Spring Kit, Folding Rops Kit			

Registered trademark and Trademark of Ariens Company, Kawasaki*, Kohler* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visitariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2017 Ariens Company. All rights reserved.